

Please type a plus sign (+) inside this box ☒

09-12-00

A

09/11/00

09/11/00

UTILITY
PATENT APPLICATION
TRANSMITTAL

Attorney Docket No.	CDS0223	Total Pages	2
First Named Inventor or Application Identifier			
Merrit N. Jacobs, et al.			
Express Mail Label No.	EI465910315US		

APPLICATION ELEMENTS

ADDRESS TO: Commissioner for Patents
Box Patent Application
Washington, DC 20231

See MPEP Chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form (attached hereto in duplicate)
2. ☒ Specification [Total Pages 23]
(Preferred arrangement set forth below)

- Descriptive Title of the Invention
- Cross References to Related Applications
- Statement Regarding Fed sponsored R&D
- Reference to Microfiche Appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure

3. ☒ Drawing(s) (35 USC 113) [Total Sheets 7]

4. Oath or Declaration

- a. ☒ Newly executed (original)
b. ☐ Unexecuted original
c. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional check boxes 5 and 16)
i. ☐ Deletion of Inventor(s)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation by Reference
(useable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)

15. ☐ Other:

16. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-Part (CIP) of prior application No:

17. For this divisional application, please cancel original Claims of the prior application before calculating the filing fee.

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label or ☒ Correspondence Address below

Name: Audley A. Ciamporzero, Jr., Esq.

Address: Johnson & Johnson
One Johnson & Johnson Plaza
New Brunswick, NJ 08933-7003 USA

19. TELEPHONE CONTACT

Please direct all telephone calls or telefaxes to Michael W. Montgomery at:

Telephone: (305) 824-2922 Fax: (305) 824-2747

19. SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME Michael W. Montgomery Reg. No. 35,958

SIGNATURE *Michael W. Montgomery*

DATE September 11, 2000

FEE TRANSMITTAL	<i>Complete if Known</i>	
	Application Number	
	Filing Date	September 11, 2000
	First Named Inventor	Merrit N. Jacobs, et al.
	Group Art Unit	
	Examiner Name	
	Attorney Docket Number	CDS0223


FEE CALCULATION

CLAIMS AS FILED

(1)	(2)	(3)	(4)	(5)
FOR:	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE \$690.00
TOTAL CLAIMS	15 - 20 =	0	x 18.00	\$ 0.00
INDEPENDENT CLAIMS	6 - 3 =	3	3 x 78.00	\$ 234.00
MULTIPLE DEPENDENT CLAIMS	<input type="checkbox"/>	N/A	\$260.00	
			TOTAL FEES	\$ 924.00

METHOD OF PAYMENT

- ☒ Please charge Deposit Account No. 10-0750/CDS0223/MWM in the amount of \$924.00. Three copies of this sheet are enclosed.
- ☒ The Commissioner is hereby authorized to charge any additional fees which may be required in connection with the filing of this communication, or credit any overpayment, to Account No. 10-0750/CDS0223/MWM. Three copies of this sheet are enclosed.

SUBMITTED BY:		<i>Complete (if applicable)</i>
Typed or Printed Name	Michael W. Montgomery	Reg. No. 35,958
Signature		Date: September 11, 2000
		Deposit Account No. 10-0750

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s): Merrit N. Jacobs
James D. Shaw

Filed: September 11, 2000
For: Analyzer With Sample Quality Measurement, And Method

Express Mail Certificate

"Express Mail" mailing number: EI465910315US

Date of Deposit: September 11, 2000

I hereby certify that this complete application, including specification pages, claims, formal drawings, signed Declaration and Power of Attorney and Invention Disclosure Statement are being deposited with the United Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.


Maria Broussard

ANALYZER WITH SAMPLE QUALITY MEASUREMENT, AND METHOD

BACKGROUND AND SUMMARY OF THE INVENTION

1. Technical Background:

5 The present invention relates generally to systems and methods for analyzing patient samples.

2. Discussion:

10 Spectrophotometric analysis is often applied to liquid samples to determine their contents. In general, the term "spectrophotometric" refers to capturing spectral response over a range of wavelengths and correlating a response for each of the wavelengths. A device that performs this analysis is referred to as a "spectrophotometer." Such spectrophotometric analysis has been performed with near-infrared and adjacent visible radiation, which is capable of ascertaining hemoglobin, glucose, albumin, lipoproteins, and many other sera components.

15 One challenge in performing spectrophotometric analysis has been that the samples are initially obtained in a variety of primary patient collection containers. These containers are usually tubes of varying diameters and lengths. In the case of a patient blood sample, the liquid is often centrifuged to separate the liquid serum or plasma from the cellular phases. Such tubes

may have a patient identification label, varying and unpredictable amounts of the sera to be analyzed in the total sample, and contain a relatively large amount of sample liquid.

Prior spectrophotometric analysis systems are adequate to meet their design criteria, and they generally aliquot a portion of the sample into a secondary container or tube of a consistent size. This technique may add complexity and increase the time required for processing in a single sample. This measure may introduce additional equipment expenses and processing delays, and may involve spectrophotometric scanning through the patient label.

Examples of successful analyzers having a spectrophotometric measurement through the metering tip are shown in (i) United States Patent number 5,846,492, entitled "Sample Quality Measurement And/Or Analyte Measurement In Dispensing Tip Of An Analyzer," issued to Jacobs et al. on December 8, 1998; and also (ii) United States Patent number 6,013,528, entitled "Analyzer Throughput Featuring Through-The-Tip Analysis," issued to Jacobs et al. on January 11, 2000, which are both incorporated by reference.

Many clinical analyzers provide a generally serial or linear path of dependent events for processing each sample. This serial procedure is generally required to be performed in a specific order, and each step must be finished before the next can begin. For example, an analyzer process might include the steps of sample handling, aspirating a portion of the sample into a metering tip, dispensing a portion of the sample onto a test element or slide, and then disposing of the tip. The time required to completely process a single sample may be referred to as the processing time, and each step of the total time can be referred to as a timing cycle or the "heartbeat."

Such an analyzer might include various components, including a sample handling bin or repository for holding primary collection containers, a metering probe or proboscis which can

move around the stations of the analyzer, one or more preferably disposable tips attached to the proboscis, and a metering pump connected to the proboscis for creating partial vacuum or partial pressure to selectively suck up into the tip or dispense a specific amount of sample liquid. In addition, analyzers often include the components required for a thin film or wet chemistry system, such as a test element supply, an incubator, reagent and assay supply, etc.

It is desirable in general to minimize the amount of the sample required for use in an analyzer, because any portion of the sample that is used for a particular operation cannot be later used for another process or operation. When the analyzer is in use, the component that actually touches the liquid of the sample is the tip.

Many of the metering tips used in analyzers are disposable, though the tip may also be permanent. Disposable tips generally have a relatively narrow cylindrical end, connected to a small cone, which is in turn connected to a larger generally cylindrical body. For optimum accuracy of the reading, and to minimize the amount of sample necessary, it is desirable to do the spectrophotometric measurement through the intermediate cone of the metering tip.

As an example, the present invention will be described in relation to clinical analyzers and sample quality measurement. However, it should be understood that the present invention relates to any apparatus or method having the features of the present invention, and is not limited to a particular type of design.

One method of incorporating a sample quality capability into an analyzer might be to insert a sample quality measurement step in between the step of aspirating the sample into the tip, and the step of dispensing the sample onto the test element. However, the sample quality measurement might take as long as the amount of time to meter the sample onto the test element. This particular method would therefore undesirably increase the length of the timing cycle of the

analyzer. In addition, this particular method would undesirably require initially aspirating a larger portion of the sample, to raise the liquid level into the intermediate cone of the metering tip. Moreover, this technique may require substantial enabling software to move the metering tip to a new location for the sample integrity reading.

5 Accordingly, the present invention preferably provides systems and methods for analyzing and/or detecting the sample and/or analytes, while the sample is in the metering tip used to aspirate the sample liquid and also dispense it onto a slide test element. In other words, the spectrophotometric analysis may be done on the sample liquid while it is still in the tip which may be converted into cuvette, without requiring an additional container or cuvette, and may
10 include a measurement of sample quality.

 A possible aspect of the present invention relates to enhancing throughput of an analyzer by conducting a sample quality measurement in a process that is parallel to the main analyzer timing cycle. The sample quality measurement may thus be arranged after a portion of the sample has already been dispensed onto the test element, and after the metering tip has been
15 removed from a proboscis. This novel method would eliminate a need for the analyzer to extend or skip a timing cycle, and may also eliminate a need for additional sample volume.

 One possible way to conduct the spectrophotometric measurement after the metering tip is removed from the proboscis is to first seal or crimp the end of the metering tip, spontaneously forming a cuvette for holding the remaining portion of the sample during the measurement.

20 An improved analyzer process according to the principles of the present invention may include the steps of sample handling, aspirating a portion of the sample into a metering tip, and dispensing a portion of the sample onto a test element or slide. Next, a proboscis holding the metering tip may move to a tip ejection position. Then, a position sensor may be used to detect

that the proboscis and metering tip have moved to the tip ejection position, and the sensor may trigger a clamp to hold the tip in position while the proboscis lifts away. Preferably after a short delay to let the sample fluid settle, a spectrophotometer reading is taken through the cone of the tip. The clamp may then be released, allowing the tip to fall into a disposal container.

5 In optional steps, a metering pump may pull sample fluid a short distance up into the tip to form a small bubble of air at the tip's end, and the end of the metering tip may be sealed to form a virtual cuvette.

Another optional step of the present invention may involve aspirating a selected auxiliary volume of sample liquid from the tip or cuvette after the sample quality measurement, and passing this auxiliary sample to a wet chemistry analyzer system. Or, rather than a wet chemistry system, the auxiliary sample may be passed to a diluter system, where it is diluted and passed on to the sample processing apparatus for repeating at least one clinical chemistry test and analysis on the diluted liquid.

Accordingly, some advantages of the present system and method include improved throughput, the capability to use much smaller sample liquid volumes, eliminating any need for a separate supply of cuvettes in addition to the metering tips. An additional advantage lies in providing for detection through a cone of the metering tip, rather than through any label that may be on a primary patient collection container.

Additional advantages of the present invention include conducting spectrophotometric analysis in a simpler and less expensive manner. Another advantage lies in obtaining results of spectrophotometric analysis in less time, without extending or omitting a timing cycle.

These and various other objects, advantages and features of the invention will become apparent from the following description and claims, when considered in conjunction with the appended drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Figure 1 is an external perspective view of an analyzer system, arranged according to the principles of the present invention;

Figure 2 is a perspective view of a portion of an analyzer system;

Figures 3-9 are partially diagrammatic views of portions of an analyzer system, illustrating operation of the analyzer according to a method of the present invention;

10 Figures 10-13 are partially diagrammatic views of portions of an analyzer system, showing in particular a cone portion of a metering tip during operation of the analyzer according to a method of the present invention;

Figure 14 is a partial perspective view of a sample handling system and a sample metering system of an analyzer; and

15 Figure 15 is a partial perspective view of a clinical chemistry system of an analyzer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following description of the preferred embodiments of the present invention is merely illustrative in nature, and as such it does not limit in any way the present invention, its application, or uses. Numerous modifications may be made by those skilled in the art without
20 departing from the true spirit and scope of the invention.

Referring to the drawings, several components of a clinical analyzer are depicted, with one of the preferred embodiments of the present invention being shown generally at 10. The illustrated analyzer 10 is of course only one of many different analyzer designs within the scope of the present invention.

5 In the illustrated embodiment, the analyzer 10 illustrated in the drawings includes a main operational unit 12 and an operator control unit 14. The operational unit 12 preferably includes an outer housing 16, a sample handling or supply system 18 for holding and organizing a series of primary patient collection containers 20, a sample metering system 22 for aspirating and dispensing portions of individual samples 24 and moving them among the various operating
10 stations of the analyzer 10, and a sample processing system 26 for conducting the desired clinical tests on and analysis of the samples 24. The operator control unit 14 preferably includes a monitor and keyboard 28 for operating the analyzer 10 as well as the computers of the analyzer 10, including for example a master computer, scheduling computer, and subsystems computers.

15 The selection of a particular design for the sample handling system 18 is not important for the present invention, but may include a holding surface or bay 30 for supporting a series of sample trays 32, each holding several primary patient collection containers 20. The sample handling system may be arranged along the lines of the sample handling system 18 shown in Figure 15, but may of course have a variety of designs. Such other designs may include a rectangular sample bay, linear sample trays, or any other suitable design.

20 The "primary patient collection container" is a container in which patient biological liquid, usually blood, is initially placed. The container is generally provided a label and processed in preparation for testing. In the case of whole blood, such processing often includes

phase separation in which liquid serum or plasma is separated from the cellular phase comprising the blood cells, usually with a gel separation barrier.

The sample metering system 22 may preferably be arranged along the lines of that shown in Figure 2, but may also have a variety of designs. The sample metering system 22 shown in Figure 2 includes a base 34 mounted for selective longitudinal movement on a horizontal rail 36, a horizontal drive mechanism (not shown), a vertical carriage 38 coupled to a vertical drive mechanism 40 for selective vertical movement with respect to the base 34, and a proboscis 42 affixed to the vertical rack 38. Essentially, the proboscis 42 can move in at least two dimensions within a vertical plane defined by the rail 36. Such a metering control system 22 is described in, for example, United States Patent number 4,340,390.

Because of the sensitive nature of the sample liquid 24, it is desirable to operate the sample metering system 22 without allowing any portion of the proboscis 42 to contact sample liquid 24. Accordingly, the analyzer 10 preferably has a supply of the tubular metering tips 44 which are preferably disposable. The metering tips 44 shown in the drawings can be removably attached to an end of the proboscis 42, and have a tubular body 46, and intermediate cone 48, and a capillary tip 50.

A metering pump 52 is operatively coupled to a lumen defined by the proboscis 42 and the metering tip 44, for selectively generating various amounts of partial vacuum and partial pressure. The metering pump 52, and therefore the metering assembly 22, is capable of using such partial vacuum and partial pressure to selectively aspirate and dispense amounts of sample liquid 24.

As will be readily evident, the material of the metering tips 44 is preferably selected to allow transmission of near-infrared and adjacent visible radiation. The metering tips 44 are

preferably free of labels, since any labeling can be done exclusively on the primary collection containers 20. Materials useful for metering tips 44 may include polymers such as polypropylene and polyethylene.

The sample processing system 26 has equipment for performing various clinical chemistry tests, which may include a thin film system having a supply of reagents and test element slides, and/or wet chemistry apparatus, and any other suitable clinical chemistry testing system. The illustrated sample processing system 26 has a supply of thin film slides, rotating incubator 56, reference fluid supply 58, electrometer 60, immuno-wash fluid system 62, and other clinical chemistry equipment shown in the drawings. The sample processing system 26 may include equipment to perform potentiometric, colorimetric or other clinical chemistry tests.

The analyzer 10 preferably includes conventional clinical chemistry for various assays that use test elements. The term "test element" means any reaction vessel in which at least one reagent has been pre-supplied, for example thin film or dry slide test elements. Such slides are described in, for example, United States Patent number 3,992,158. Another example of a test element would include a cup or well having a cavity pre-coated with one or more antibodies, as is described in United States Patent number 5,441,895.

In operation, the sample metering system 22 moves about the analyzer 10 among the various operating stations in a cyclical, periodic manner. First, the sample metering system 22 moves from an initial or home position to a position above a tray of disposable metering tips 44, where the proboscis 42 descends into and picks up a metering tip 44 from the tip tray. The sample metering system 22 then moves the proboscis 42 over the sample handling system 18. The proboscis 42 descends and inserts the metering tip 44 into a primary collection container 20.

The metering pump 52 creates a partial vacuum, and a portion of the patient sample 24 is aspirated into the tip 44.

Next, the sample metering system 22 moves over a test element, the metering pump 50 creates a partial pressure, and a portion of the sample liquid 24 in the metering tip 44 is dispensed onto the test element. Thereafter, the test element may be transferred to an incubator 56 where it incubates (possibly also with rotation of the incubator), until it is read or detected at a test station. The test station may generally include a colorimetric or potentiometric detector.

Additional steps and processes may be performed by the sample processing system 26 in a conventional manner. When finished, the timing cycle repeats. The time required to complete such a cycle defines the heartbeat of the analyzer.

One proposal that has been considered is to simply incorporate sample quality measurements into the timing cycle of the analyzer, in a serial manner. However, such a serial approach would undesirably lengthen the timing cycle, or require the analyzer to skip a timing cycle to conduct the sample quality measurement. This approach would thus cause an undesirable decrease in analyzer throughput, since the sample quality reading would take as much time as metering a sample onto a new test element.

This approach would also require substantial analyzer software modifications, to enable the proboscis 42 and metering tip 44 to move to a new location where the sample integrity read block is positioned. Also, additional sample fluid would be required, because the level of the sample fluid must be in the cone of the metering tip for an accurate reading.

Accordingly, the sample quality system of the present invention provides the novel concept of conducting the sample quality measurement in a parallel process to the conventional sample processing system. The concept is to have a sample quality device grab the tip as the

metering system is about to eject it. This parallel process enables the sample quality system to take several seconds to move the tip into position, make the sample quality reading, and dispose of the tip without impacting the analyzer timing cycle or throughput.

One example of the novel sample quality system 62 of the present invention is shown in the drawings. In particular, operation of a sample quality system 62 is depicted in Figures 3-13. Figures 3-5 show the proboscis 42 before and after picking up a disposable metering tip 44, and then after some sample liquid 24 has been aspirated into the tip 44.

Another novel feature of the present invention is illustrated in Figures 6-9, which occur after the sample processing system 26 has conducted the various operations and tests during a normal timing cycle, and before the tip 44 is removed from the proboscis 42 and eventually discarded. According to this novel feature, the sample quality system 62 will first crimp the end of the tip 44 to prevent sample fluid from being lost during and after the tip ejection process. As a result, the crimped tip essentially becomes a virtual cuvette 64 for holding the sample fluid.

The sample quality system 62 can then perform an absorption measurement while the sample metering system 22 is picking up the next tip 44 and aspirating fluid 24, continuing the primary timing cycle.

These additional steps are illustrated in Figures 6-9. First, the sample liquid 24 is further aspirated to a slightly higher level in the metering tip 44, leaving a portion of the capillary tip 50 empty of fluid 24. Any suitable type of heated die or clamp 66 may be used to seal a portion of the capillary tip 50. Following removal of the metering tip 44 from the proboscis 42, the metering tip 44 is sealed and becomes a cuvette 64 as shown in Figure 8, and the sample quality measurement is performed as shown in Figure 9.

The sample quality measurement of the present invention is performed by a spectrophotometer 68. The spectrophotometer 68 is shown only diagrammatically in the drawings, and it is not described in any detail, because any suitable spectrophotometer may be used, provided it operates acceptably and is preferably responsive to radiation in the near-infrared and adjacent visible light regions with sufficient precision. The term "near-infrared and adjacent visible radiation" or light means radiation between about 400 and 2500 nm, and preferably between about 475 and 1075 nm. Useful translucent or transparent materials for the metering tips that allow desired spectral penetration are those commonly used to manufacture clinical analyzer disposable tips, including polypropylene and polyethylene.

In operation, the cuvette 64 is positioned at the sample quality station, and a beam of preferably near-infrared and adjacent visible wavelengths is passed through the cuvette 64 and any liquid inside. The radiation transmitted is spectrophotometrically analyzed by the spectrophotometer 68. The signal produced by the detector is then correlated with the concentration of target substances.

A preferred set of target substances are those that indicate sample quality, specifically those selected from the group consisting of hemoglobin, lipids, bilirubin, and biliverdin. However, any target substance capable of spectrophotometric detection by its absorption spectra can be correlated and detected by this invention. More specifically, certain assays that have previously been conducted on the slide test element, can now be conducted through the tip spectrophotometrically.

In addition to testing for sample quality, any target substance that is analyzable spectrophotometrically, preferably by using near-infrared and adjacent visible wavelengths, can be analyzed by the spectrophotometer while the patient sample is in the metering tip. Such

possible target substances include hemoglobin, albumin and glucose, among others. By testing these target substances in the tip, it is not necessary to conduct (and the analyzer preferably omits), further assays for them when the sample is tested by the sample processing system during the normal timing cycle.

5 This technique enhances greatly the total throughput of the analyzer 10, because the spectrophotometric detection is performed in a parallel process from the standard analyzer process. Also, the spectrophotometric measurement through the tip 44 may require only about four seconds for all the target substances, compared to about four seconds for each separate assay performed on a slide test element. In addition, the "time to result" is also improved by
10 spectrophotometric analysis through the tip to approximately four seconds for analysis through the tip, compared to approximately five minutes on a slide test element.

Testing in this manner while sample liquid is in the metering tip may also be done with some kind of temperature control. Such sample liquid temperature control may be done by controlling the temperature at the test station, but can also be done by heating or cooling the
15 sample liquid in the primary containers, or while the liquid is in the metering tip, etc.

Although the tests conducted by the sample processing system 26 preferably omits those spectrophotometric tests done through the tip 44, it is also possible to repeat such assays during the primary timing cycle, to obtain a check of their accuracy.

In addition, another optional step of the present invention may involve aspirating a
20 selected auxiliary volume of sample liquid from the tip or cuvette after the sample quality measurement, and passing this auxiliary sample to a wet chemistry analyzer system. Moreover, rather than a wet chemistry system, the auxiliary sample may be passed to a diluter system, where

it is diluted and passed on to the sample processing apparatus for repeating at least one clinical chemistry test and analysis on the diluted liquid.

It should be understood that an unlimited number of configurations for the present invention could be realized. The foregoing discussion describes merely exemplary embodiments

5 illustrating the principles of the present invention, the scope of which is recited in the following claims. Those skilled in the art will readily recognize from the description, claims, and drawings that numerous changes and modifications can be made without departing from the spirit and scope of the invention.

CLAIMS

What is claimed is:

1. A method of performing spectrophotometric analysis on a portion of a liquid sample in a clinical analyzer, comprising the steps of:

5 providing one or more sample containers holding an amount of sample liquid, and providing a clinical analyzer with a sample handler, a metering system, a supply of reagents; and simultaneously performing repeating cycles of a first clinical chemistry process conducting clinical tests, and a parallel spectrophotometry process conducting spectrophotometric analysis;

10 wherein at least a portion of sample liquid is passed from the first clinical chemistry process to the spectrophotometry process.

2. A method of performing measurements on at least a portion of a liquid sample in a clinical analyzer, comprising the steps of:

15 (a) providing a clinical analyzer with sample handling apparatus having one or more sample containers holding an amount of sample liquid; with sample metering apparatus having a proboscis, one or more metering tips having a tubular shape with a metering aperture at one end, a metering pump coupled with the proboscis; and sample processing apparatus having one or more test elements;

20 (b) attaching a tip to the proboscis to create a metering assembly;

(c) moving the metering assembly to an initial aspiration position, in which the metering aperture of the tip is immersed in sample liquid;

(d) creating a partial vacuum with the metering pump, causing a selected volume of sample liquid to be aspirated from a sample container into the tip;

(e) moving the metering assembly to a dispensing position;

(f) creating a partial pressure with the metering pump, causing a portion of the sample liquid to be dispensed from the metering tip onto a test element;

(g) the sample processing apparatus then performing at least one clinical chemistry test and analysis;

(h) the metering assembly moving to a tip ejection position;

(i) removing the metering tip from the proboscis;

(j) performing a sample quality measurement on the sample liquid in the ejected tip;

wherein said steps (b)-(h) are repeated in a primary analyzer cycle; wherein said steps (h)-(j) are repeated in a secondary sample quality cycle; such that at least portions of the primary and secondary cycles occur simultaneously.

3. The method of Claim 2, wherein the test elements are thin film slides.

4. The method of Claim 2, wherein the step of performing a sample quality measurement includes performing at least one additional test that is also conducted during said step of performing clinical chemistry tests, further comprising the additional step of:

comparing the results of the tests, and using the comparison to calibrate the analyzer.

5. The method of Claim 2, wherein the sample quality measurement is performed by a spectrophotometer.

6. A method of performing measurements on at least a portion of a liquid sample in a clinical analyzer, comprising the steps of:

(a) providing a clinical analyzer with sample handling apparatus having one or more sample containers holding an amount of sample liquid; with sample metering apparatus having a proboscis, one or more metering tips having a tubular shape with a metering aperture at one end, a metering pump coupled with the proboscis; and sample processing apparatus having one or more test elements;

(b) attaching a tip to the proboscis to create a metering assembly;

(c) moving the metering assembly to an initial aspiration position, in which the metering aperture of the tip is immersed in sample liquid;

(d) creating a partial vacuum with the metering pump, causing a selected volume of sample liquid to be aspirated from a sample container into the tip;

(e) moving the metering assembly to a dispensing position;

(f) creating a partial pressure with the metering pump, causing a portion of the sample liquid to be dispensed from the metering tip onto a test element;

(g) the sample processing apparatus then performing at least one clinical chemistry test and analysis;

(h) the metering assembly moving to a tip ejection position;

(i) removing the metering tip from the proboscis;

(j) performing a spectrophotometric measurement on the sample liquid in the ejected tip;

wherein said steps (b)-(h) are repeated in a primary analyzer cycle; wherein said steps (h)-(j) are repeated in a secondary spectrophotometric cycle; such that at least portions of the primary and secondary cycles occur simultaneously.

7. The method of Claim 6, whereby the throughput of the analyzer is increased to a rate greater than a serial method of operating an analyzer.

8. The method of Claim 6, wherein the tips have a tubular body and a capillary tip, connected by a cone; such that the sample quality measurement is performed through the cone of the tip.

9. The method of Claim 6, wherein at least some of said steps are conducted automatically by a computer.

10. The method of Claim 6, wherein the sample quality measurement step includes measuring hemoglobin, lipids, bilirubin, and biliverdin.

11. A method of analyzing a portion of a liquid sample in a clinical analyzer, comprising the steps of:

providing one or more sample containers holding an amount of sample liquid, and providing a clinical analyzer with a sample handler, a metering system, a supply of reagents; and

simultaneously performing repeating cycles of a first clinical chemistry process conducting clinical tests, a parallel spectrophotometry process conducting spectrophotometric analysis, and a parallel second clinical chemistry process conducting clinical tests;

wherein at least a portion of sample liquid is passed from the first clinical chemistry process to the spectrophotometry process, and at least a portion of sample liquid is passed from the spectrophotometry process to the second clinical chemistry process.

12. A method of performing measurements on at least a portion of a liquid sample in a clinical analyzer, comprising the steps of:

(a) providing a clinical analyzer with sample handling apparatus having one or more sample containers holding an amount of sample liquid; with sample metering apparatus having a proboscis, one or more metering tips having a tubular shape with a metering aperture at one end, a metering pump coupled with the proboscis; and sample processing apparatus having one or more test elements;

(b) attaching a tip to the proboscis to create a metering assembly;

(c) moving the metering assembly to an initial aspiration position, in which the metering aperture of the tip is immersed in sample liquid;

(d) creating a partial vacuum with the metering pump, causing a selected volume of sample liquid to be aspirated from a sample container into the tip;

(e) moving the metering assembly to a dispensing position;

(f) creating a partial pressure with the metering pump, causing a portion of the sample liquid to be dispensed from the metering tip onto a test element;

(g) the sample processing apparatus then performing at least one clinical chemistry test and analysis;

(h) the metering assembly moving to a tip ejection position;

(i) removing the metering tip from the proboscis;

5 (j) performing a sample quality measurement on the sample liquid in the ejected tip;

(k) aspirating a selected auxiliary volume of sample liquid from the tip;

wherein said steps (b)-(h) are repeated in a primary analyzer cycle; wherein said steps (h)-(j) are repeated in a secondary sample quality cycle; such that at least portions of the
10 primary and secondary cycles occur simultaneously.

13. The method of Claim 12, further comprising the step of:

(l) passing the auxiliary volume of sample liquid to a wet chemistry analyzer system.
15

14. The method of Claim 12, further comprising the steps of:

(l) passing the auxiliary volume of sample liquid to a diluter system;

(m) diluting the auxiliary volume of sample liquid to form a diluted liquid;

(n) passing the diluted liquid to the sample processing apparatus; and

20 (o) the sample processing apparatus then performing at least one clinical chemistry test and analysis on the diluted liquid.

15. A clinical analyzer for analyzing at least a portion of a liquid sample, comprising:
sample handling apparatus having one or more sample containers holding an
amount of sample liquid;

sample metering apparatus having a proboscis defining a metering lumen, one or
5 more tips with a tubular shape and a metering aperture at one end, and a metering pump coupled
with the proboscis lumen; the tips being removably attachable to the proboscis and allowing fluid
communication between the metering pump and the metering aperture through the proboscis
lumen;

sample processing apparatus having one or more test elements, an incubator and at
10 least a thin film clinical chemistry system and a wet chemistry clinical testing system for
conducting clinical tests on the liquid samples; and

sample quality apparatus having a spectrophotometer and a tip end clamping
device;

the analyzer having several operating stations:

15 (a) an initial aspiration position where a metering aperture of the tip can be
periodically immersed in sample liquid held within one of the sample
containers; the metering pump adapted to create a partial vacuum to cause
a selected volume of sample liquid to be aspirated from a sample container
into the tip;

20 (b) a dispensing position where the metering pump can create a partial
pressure to cause a portion of the sample liquid to be dispensed from the
tip onto a test element;

(c) a thin film clinical chemistry testing position;

- (d) a sample quality measurement position;
- (e) a wet chemistry testing position.

ANALYZER WITH SAMPLE QUALITY MEASUREMENT, AND METHOD

ABSTRACT OF THE DISCLOSURE

A system for detecting and analyzing patient sample quality and/or analytes, while the sample is in the metering tip used to aspirate the sample liquid from an original patient sample container, and also to dispense the liquid onto a slide test element. Spectrophotometric analysis may be done on the sample liquid while it is still in the tip which has been converted into a cuvette. One technique for such analysis is by scanning the cuvette for transmittance in a light-tight enclosure. Near-infrared and adjacent visible radiation may be used, and the absorption spectra of the liquid detected and analyzed. A possible aspect of the present invention relates to enhancing throughput of an analyzer by conducting a sample quality measurement in a process that is parallel to the main analyzer timing cycle. Another possible aspect of the present invention relates to improving performance of the analyzer by sealing the end of the metering tip to spontaneously form a cuvette for holding the sample during the sample quality measurement. Some advantages of the present system and method include improved throughput, the capability to use smaller sample liquid volumes, eliminating any need for a separate supply of cuvettes independent of the metering tips, and providing for detection through a cone of the metering tip rather than through any label, compared to doing the scanning of the sample liquid in a primary patient collection container.




Figure - 1

FIG. 1 is a perspective view of a portable electronic device, such as a medical ultrasound machine, in an open position.




Figure - 2




Figure - 3




Figure - 4




Figure - 5







Figure - 6






Figure - 10




Figure - 11




Figure - 12




Figure - 13




Figure - 14




Figure - 15

DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled "Analyzer With Sample Quality Measurement, And Method".

The specification of which

(check one) ☒ is attached hereto.

[] was filed on as

Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

Country	Application Number	Date of Filing	Priority Claimed Under 35 U.S.C. 119
		Day/Mo./Year	<input type="checkbox"/> YES <input type="checkbox"/> NO
		Day/Mo./Year	<input type="checkbox"/> YES <input type="checkbox"/> NO
		Day/Mo./Year	<input type="checkbox"/> YES <input type="checkbox"/> NO

I hereby claim the benefit under Title 35, United States Codes §119(e) of any United States provisional application(s) listed below.

(Application Number)

(Filing Date)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.

Filing Date

Status

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith as well as to file equivalent patent applications in countries foreign to the United States including the filing of international patent applications in accordance with the Patent Cooperation Treaty: Audley A. Ciamporcero, Jr. (Reg.#26,051), Steven P. Berman (Reg.#24,772), Andrea L. Colby (Reg. #30,194), Paul A. Coletti (Reg. #32,019), Matthew S. Goodwin (Reg. #32,839), Ralph S. Palo (Reg. #29,486), Bernard F. Plantz (Reg. #32,091), Joseph F. Shirtz (Reg. #31,880), Michael Stark (Reg. #32,495), Michael Q. Tatlow (Reg. #20,501), Henry W. Collins (Reg. #25,039), Dean L. Garner (Reg. #35,877) and Michael W. Montgomery (Reg. #35,958), One Johnson & Johnson Plaza, New Brunswick, NJ 08933.

Address all telephone calls to Michael W. Montgomery at telephone No. (305) 824-2922.


Address all correspondence to Audley A. Ciamporcero, Jr., One Johnson & Johnson Plaza, New Brunswick, NJ 08933-7003.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Inventor's Signature:

Full Name of Sole

or First Inventor


Merrit N. Jacobs

Date: 25 Aug 00

Citizenship:

Residence:


Post Office Address:

United States of America
3 Foxboro Terrace
Fairport, New York 14450
(Same as residence)

Inventor's Signature:

Full Name of Second Joint

Inventor


James D. Shaw

Date: 25 Aug 00

Citizenship:

Residence:

Post Office Address:

United States of America
58 Hogan Point Road
Hilton, New York 14468
(Same as residence)